

WM-NP3 Mobile Workstation



WM-NP3 Workstation

Features

The WM-NP3 has been designed and manufactured to enhance the user experience and add value to the Olympus Imaging Platform systems. Using a slim line profile, increased loading capacity whilst taking up less floor space and lower running costs, the WM-NP3 will support Olympus Systems without dominating the Clinical Environment making it a valuable successor to WM-NP2.

Customisation

Dedicated accessories are available to optimise system and procedural efficiency.

Electrical Safety

The WM-NP3 is supplied with a separation transformer as standard. Output from the transformer is controlled using the central on/off switch allowing all equipment to be powered up simultaneously.

Inrush current control & Low Power Standby

The WM-NP3 uses a level detector to detect mains distortion and protect the transformer from inrush current. The inrush current protection system is powered from a medically approved AC-DC power supply. To reduce the Environmental impact of the WM-NP3, the low power standby mode reduces standby power consumption giving greater efficiency and energy saving.

Easy to Move

Ergonomically designed handles and twin wheeled castors allow the workstation to be moved into the ideal position in the Clinical Environment.

Cable Management

Optimised cable management has been achieved by locating the cable management modules within the workstation hoop increasing the cable capacity and providing access to route and remove cables easily.

Imaging

The WM-NP3 workstation is offered with a choice of Monitor arm that optimises the range of compatible monitors and enhances the procedural view with both swivel and tilt functionality. The MAJ-2216 has a weight range between 6.5kg and 12kg and the MAJ-2217 has a weight range between 12kg and 14kg. Using a VESA fitting, both arms will accommodate a monitor up to 32".



WM-NP3 Workstation

Accessories

MAJ-2154

Consumable storage holder



Article number - K10030423

MAJ-2158

Suction jar holder



Article number - K10028139

MAJ-2159

Scope pole kit



Article number - K10028140

MAJ-2160

Irrigation Tube Holder



Article number - K10028141

MAJ-2165

Drawer unit



Article number - K10030178

MAJ-2166

Sterile water holder



Article number - K10030036

MAJ-2167

Nurses control arm



Article number - K10030210

MAJ-2173

Side shelf



Article number - K10030389

MAJ-2211

Side handles



Article number - K10035108

MAJ-2216

LCD monitor arm 6.5 kg - 12 kg



Article number - K10035789

WM-NP3

Standard Sets include:

WM-NP3 Workstation plus items marked (•)

MAJ Number	Part Description	Article Number	Region	Basic Set	GI Standard	URO Set
			EUROPE JAPAN UK US ROW	K10035360 K10035362 K10029987 K10035361 K10035363	K10035365 K10035367 K10035364 K10035366 K10035368	K10035370 - - K10035371 K10035373
	Workstation Fitting Kit			•	•	•
	Transformer (market specific)			•	•	•
MAJ-2160	Irrigation Tube Holder	K10028141		•	•	•
MAJ-2146	Sliding Keyboard Tray	K10027573			•	•
MAJ-2159	Scope Pole Kit	K10028140			•	
MAJ-2216	LCD Monitor Arm 6.5 kg - 12 kg	K10035789			•	
MAJ-2211	Side Handles	K10035108			•	•
	IEC Lead Set	K10009210		•	•	•
MAJ-150	Adaptor Cable (USA / Japan only)	K100		•	•	•
	Instruction Manual	K10035968		•	•	•

Optional Compatible Accessories:

Article Number	MAJ Number	Part Description
K10021041	MAJ-1639	CO ₂ Cylinder Holder-140
K10016952	MAJ-1642	IV Pole
K10021042	MAJ-1650	CO ₂ Cylinder Holder-205
K10021043	MAJ-1653	CO ₂ Cylinder Holder-Double
K10021352	MAJ-1654	Equipotential Terminal Strip
K10021791	MAJ-1657	Keyboard Arm Side Mounted
K10021795	MAJ-1661	Side Mounted LCD Monitor Arm
K10021797	MAJ-1663	EUS Arm Mount Kit
K10022056	MAJ-1665	Camera Head Holder
K10027573	MAJ-2146	Sliding Keyboard Tray
K10027575	MAJ-2149	Dual Monitor Arm

Specifications

WM-NP3

Dimensions	1400 mm (H) x 675 mm (D) x 665 mm (W)
Weight	84 kg (unladen) including fitted transformer
Max load capacity	Maximum 20 kg on top tray
	Maximum 31 kg per shelf
	Maximum 35 kg on base panel
Castors	125 mm diameter
	2 x Braked conductive twin wheeled castors
	2 x Braked twin wheeled castors

Voltage

The WM-NP3 is supplied with a separation transformer based on one of the following voltage options:

MAJ-2155	WM-T3 Transformer 100V
MAJ-2156	WM-T3 Transformer 110-120V
MAJ-2157	WM-T3 Transformer 220-240V

Construction

Workstation

Hoop	Extruded profiled aluminium
Shelves	Mild steel
Top Tray	Injection moulded ABS

Specifications, design and accessories are subject to change without any notice or obligation on the part of the manufacturer.

OLYMPUS

OLYMPUS MEDICAL
KeyMed House, Stock Road, Southend-on-Sea, Essex, SS2 5QH, United Kingdom
Tel +44 (0)1702 616333 | www.olympus.co.uk

For a complete listing of sales and distribution locations visit:
www.olympus.com